

Life-Cycle Assessment of Different Powertrain Technologies for Light- and Heavy-Duty Vehicles

Dirk Bosteels • 16th Int. ECT Conference • 7-8 October 2025

AECC is now the Association for Emissions Control and Climate

Expanding the scope

Components and systems

Full and Associate member companies

- Air quality and Climate requirements
- Mobile and Stationary emissions sources
- Sustainable components and systems
- Catalysts
- Filters
- Adsorbers

- Fuel cells
- Electrolysers
- System integration















EU Transparency Register #78711786419-61, consultative status with the UN Economic and Social Council (ECOSOC)




AECC works in partnership with EU policymakers to target

Zero-impact pollutant emissions



Net-zero
Greenhouse
gas emissions



AECC member emission control systems ensure there's no measurable negative impact of these gases on the environment or on public health



AECC member emission control systems are compatible with CO₂-neutral fuels for a closed carbon cycle



LCA and LDV/HDV CO₂ reviews are a key AECC activity













AECC is member of EU road-vehicle industry working groups

- Working group on Monitoring Methodologies (also known as 'Stuttgart group')
 - Evaluates all mechanical and digital solutions for monitoring the use of CO₂-neutral fuels
 - Published first <u>report</u> on 11 December 2024

- Network for Sustainable Mobility
 - Informal group of EU associations
 - Discussion of ad-hoc joint statements on topics related to the use of sustainable renewable fuels







AECC understanding of the EU CO₂ emissions review schedule

- LD CO₂ emissions
 - Commission proposal amending Reg. (EU) 2017/1151
 - Adding vehicle category running exclusively on CO₂-neutral fuels
 - Discussions in TCMV on Euro 6 stopped, expected to reconvene for Euro 7 following CO₂ review
 - Regulation (EU) 2023/851
 - Article 7a life cycle assessment methodology by 31 December 2025
 - Article 14a Progress report by 31 December 2025
 - Article 15 Review of effectiveness and impact by Q2/2026
- HD CO₂ emissions
 - Regulation (EU) 2024/1610 Article 15
 - Assessment of sustainable renewable fuels by 31 December 2025
 - Review of effectiveness and impact by 31 December 2027, including
 - Role of carbon correction factor
 - Life cycle assessment methodology
 - Methodology for registering vehicles running exclusively on CO₂-neutral fuels



Life-Cycle Assessment method development

- European Commission, DG-CLIMA
 - Work supported by a consortium of Ricardo, Öko-Institut, TU Graz and IVL Sweden
 - Build on existing EU legislative references and UNECE A-LCA IWG
 - Scope
 - All LDV vehicle technologies and powertrains in the EU according to cradle-to-grave method
 - HDV in second step
 - Initial goal: voluntary OEM reporting, feeding into the bi-annual EC progress report
- UNECE A-LCA
 - Timeline for drafting until GRPE adoption (WP.29 adoption to follow)





AECC and **IPA** LCA study

- Objectives
 - Extending the Well-to-Wheel CO₂ emissions of AECC-IPA LDV/HDV demonstrators on CO₂-neutral fuels
 - Understand impact of LCA methodology choices under consideration by UNECE and EU
- Conducted by Joanneum Research







J. Demuynck, et al.; Life Cycle Assessment (LCA) of Light- and Heavy-duty Vehicles, SIA Powertrain Conference 2025




AECC and **IPA** LCA study

- Scope
 - Level 1-2 LCA study (levels under consideration at UNECE A-LCA IWG)

- Impact categories investigated
 - Global Warming Potential (GWP CO₂eq/km)
 - Including impact of CO₂, CH₄ and N₂O
 - Primary Energy Demand (PED kWh/km)
 - Several additional impact categories possible







AECC and **IPA LCA** study


- Scope
 - Vehicles
 - Passenger cars, based on GreenNCAP vehicles representative for AECC demonstrators
 - Trucks, based on IEA Task 46 vehicle representative for AECC demonstrator
 - Powertrains
 - Energy sources
 - Variation in use phase only

Powertrain	Energy sources		Cars	Trucks
	Current	100% Renewable		
ICE	B7 diesel	HVO UCO (Used Cooking Oil) E-diesel (wind and Direct Air Capture)	X	X
ICE	Gasoline E10	E-gasoline E10 (wind and Direct Air Capture)	X	
PHEV	Gasoline E10	E-gasoline E10 (wind and Direct Air Capture)	X	
BEV	EU27	Wind	X	X
H ₂ ICE	-	Wind electrolysis		X
H ₂ FCEV	-	Wind electrolysis		X



All LDV powertrains have similarly low GHG emissions

- When operated on renewable electricity/fuel
- ICE and BEV have similar emissions for production of vehicle body
 - Emissions of battery production are additionally significant for BEV
- Remaining ICE emissions are mainly from fuel supply and combustion
 - Combustion becomes net-zero in case of e-fuel or HVO (UCO)
- Remaining BEV emissions are from electricity supply




Key assumptions

- GreenNCAP LCA methodology
- C-segment vehicle
- Production: 2024 global average
- Fuel/energy varied only in use phase
- Lifetime: 240k km, 16 years
- E-gasoline from wind & DAC
- HVO from Used Cooking Oil
- CO_{2eq} incl. CO_2 , CH_4 and N_2O



Mixed picture for Primary Energy Demand


- Primary Energy Demand (PED) represents the amount of energy needed to drive a km
- BEV on wind and ICE on HVO (UCO) have the lowest PED from those powertrain options that are relying on renewables sources
- ICE on e-gasoline has higher PED
 - Requiring a higher amount of renewable energy sources
 - But fuel can be energy carrier of renewable energy sources elsewhere in the world





All HDV powertrains have similarly low GHG emissions

- When operated on renewable electricity/ fuel
- ICE, FCEV and BEV have similar emissions for production of vehicle body
 - Emissions of battery production or H₂ tank are additionally significant for ICE, FCEV and BEV
- Remaining ICE emissions are mainly from fuel supply and combustion
 - Combustion becomes net-zero in case of e-fuel, H₂ or HVO (UCO)
- Remaining FCEV and BEV emissions are from H₂ or electricity supply




Key assumptions

- GreenNCAP LCA methodology
- N3 truck IEA Task 46
- Production: 2024 global average
- Fuel/energy varied only in use phase
- Lifetime: 1.2m km, 12 years
- E-diesel from wind & DAC
- HVO from Used Cooking Oil
- CO_{2eq} incl. CO₂, CH₄ and N₂O



Mixed picture for Primary Energy Demand

- BEV on wind and ICE on HVO (UCO) have the lowest PED from those powertrain options that are relying on renewables sources
- H₂ ICE and FCEV have higher PED, requiring higher amount of renewable sources
- ICE on e-diesel has highest PED, requiring highest amount of renewable sources
- H₂ and e-diesel can be energy carriers for renewable energy sources elsewhere in the world






Summary and outlook

LCA results

- Only 2 out of many impact categories investigated
- Results show no "Zero-GHG emissions" vehicle, but all powertrains show similarly low GHG emissions when further developing technologies for biofuels, e-fuels, renewable electricity and hydrogen
- ICE on 'HVO from UCO' and BEV on 'wind' have lowest Primary Energy Demand
- ICE on H₂/e-fuels and FCEV have higher Primary Energy Demand, but can be energy carriers for renewable energy sources elsewhere in the world
- LCA methodologies
 - Transparent reporting is needed for base characteristics of
 - Vehicle
 - Powertrain
 - Energy and fuels





THANK YOU!





AECC AISBL

Rue Belliard 40 b24 B-1040 Brussels, Belgium

Methodologies investigated

- Levelling concept 1 4
- Additional GHG species (next to CO₂, CH₄ and N₂O)
 - Focus on global warming potential of H₂
 - Gaseous storage and transportation
 - Liquid storage and transportation
- Allocation of emissions in case of co-products, e.g. biofuels
 - System expansion
 - Energy allocation
- End-of-Life modelling
 - Substitution of primary material
 - Circular Footprint Formula
- Relevance of infrastructure



Need for transparent reporting

- Most significant methodology impact is from base characteristics
 - Powertrain energy consumption
 - Vehicle mileage (km) definition
 - Others
 - Vehicle weight
 - Powertrain battery capacity
 - Energy/fuel emission factors

E10

ICE

Range according to GreenNCAP measurements

EU27

BEV

